

DS2818 LCR 自动测量仪 LCR Meter

- 适用于各种元件的参数测量
Suitable for parameter measurement of various components
- 选配打印机 RS232C 接口和 HANDLER 接口
Optional printer RS232C interface and HANDLER interface



DS2818

主要技术指标 Main Specifications

型号	DS2818
测试频率 Test frequency	50Hz-300KHz (2 万个频率点 frequency points)
测试速率 Measuring speed	快速 Fast:7-15meas/sec 中速 Mid:7-8meas/sec 慢速 Slow:3-4meas/sec
测量范围 Measurement display range	R/X/Z : 0.00001Ω ~ 99.9999MΩ C : 0.00001pF ~ 9999.99mF L : 0.00001μH ~ 9999.99H D : 0.00001 ~ 9.99999 Q : 0.00001 ~ 99999.9
测量精度 Basic accuracy	±0.05%
量程 Range	9 个量程，自动与手动 9 ranges with AUTO and MANUAL modes
信号源内阻 Internal resistance of signal source	可选 30Ω或 100Ω 30Ω或 100Ω can be selected
测试信号电平 Level of tested signal	10mV-2V, 10mV 步进 stepping
显示方式 Display	240*128 LCD 液晶 直读、百分比 Direct and % reading
其他功能 Other functions	10 档分选，分选档数可设定 10 gears and number of the gears can be set up 有报警模式 With alert function 选配打印机 RS232C 接口和 HANDLER Optional RS232C and HANDLER interfaces